



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/708,913	03/31/2004	Richard Evans Monivis		2912

7590 06/05/2006
Richard Evans Monivis
10351 S.W. 64 Street
Miami, FL 33173

EXAMINER

MAI, TRI M

ART UNIT	PAPER NUMBER
----------	--------------

3727

DATE MAILED: 06/05/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Applicati n N . 10/708,913	Applicant(s) MONIVIS, RICHARD EVANS	
	Examiner Tri M. Mai	Art Unit 3727	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --
Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☐ Responsive to communication(s) filed on ____.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-12 is/are pending in the application.
4a) Of the above claim(s) ____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) ____ is/are allowed.
- 6) ☒ Claim(s) 1-12 is/are rejected.
- 7) ☐ Claim(s) ____ is/are objected to.
- 8) ☐ Claim(s) ____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on ____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. ____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. ____. |
| 2) <input type="checkbox"/> Notice of Draftperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date ____. | 6) <input type="checkbox"/> Other: ____. |

DETAILED ACTION

Drawings

(a) Drawings . There are two acceptable categories for presenting drawings in utility patent applications:

(1) Black ink . Black and white drawings are normally required. India ink, or its equivalent that secures solid black lines, must be used for drawings, or

**>(c) Identification of drawings . Identifying indicia, if provided, should include the application number or the title of the invention, inventor's name, docket number (if any), and the name and telephone number of a person to call if the Office is unable to match the drawings to the proper application. This information should be placed on the back of each sheet of drawings a minimum distance of 1.5 cm. (5/8 inch) down from the top of the page. In addition, a reference to the application number, or, if an application number has not been assigned, the inventor's name, may be included in the left - hand corner provided that the reference appears within 1.5cm. (9/16 inch) from the top of the sheet.<

**>(f) Size of paper . All drawing sheets in an application must be the same size. One of the shorter sides of the sheet is regarded as its top. The size of the sheets on which drawings are made must be:

- (1) 21.0 cm. by 29.7 cm. (DIN size A4), or
- (2) 21.6 cm. by 27.9 cm. (8 1/2 by 11 inches).

(g) Margins . The sheets must not contain frames around the sight; i.e., the usable surface, but should have scan target points, i.e., cross - hairs, printed on two catercorner margin corners. Each sheet must include a top margin of at least 2.5 cm. (1 inch), a left side margin of at least 2.5 cm. (1 inch), a right side margin of at least 1.5 cm. (9/16 inch), and a bottom margin of at least 1.0 cm. (3/8 inch), thereby leaving a sight no greater than 17.0 cm. by 26.2 cm. on 21.0 cm. by 29.7 cm. (DIN size A4) drawing sheets, and a sight no greater than 17.6 cm. by 24.4 cm. (6 15 / 16 by 9 5/8 inches) on 21.6 cm. by 27.9 cm. (8 1/2 by 11 inch) drawing sheets.<

(h) Views . The drawing must contain as many views as necessary to show the invention. The views may be plan, elevation, section, or perspective views. Detail views of portions of elements, on a larger scale if necessary, may also be used. All views of the drawing must be grouped together and arranged on the sheet(s) without wasting space, preferably in an upright position, clearly separated from one another, and must not be included in the sheets containing the specifications, claims, or abstract. Views must not be connected by projection lines and must not contain center lines. Waveforms of electrical signals may be connected by dashed lines to show the relative timing of the waveforms.

Art Unit: 3727

(1) Exploded views . Exploded views, with the separated parts embraced by a bracket, to show the relationship or order of assembly of various parts are permissible. When an exploded view is shown in a figure which is on the same sheet as another figure, the exploded view should be placed in brackets.

(2) Partial views . When necessary, a view of a large machine or device in its entirety may be broken into partial views on a single sheet, or extended over several sheets if there is no loss in facility of understanding the view. Partial views drawn on separate sheets must always be capable of being linked edge to edge so that no partial view contains parts of another partial view. A smaller scale view should be included showing the whole formed by the partial views and indicating the positions of the parts shown. When a portion of a view is enlarged for magnification purposes, the view and the enlarged view must each be labeled as separate views.

(i) Where views on two or more sheets form, in effect, a single complete view, the views on the several sheets must be so arranged that the complete figure can be assembled without concealing any part of any of the views appearing on the various sheets.

(ii) A very long view may be divided into several parts placed one above the other on a single sheet. However, the relationship between the different parts must be clear and unambiguous.

(3) Sectional views . The plane upon which a sectional view is taken should be indicated on the view from which the section is cut by a broken line. The ends of the broken line should be designated by Arabic or Roman numerals corresponding to the view number of the sectional view, and should have arrows to indicate the direction of sight. Hatching must be used to indicate section portions of an object, and must be made by regularly spaced oblique parallel lines spaced sufficiently apart to enable the lines to be distinguished without difficulty. Hatching should not impede the clear reading of the reference characters and lead lines. If it is not possible to place reference characters outside the hatched area, the hatching may be broken off wherever reference characters are inserted. Hatching must be at a substantial angle to the surrounding axes or principal lines, preferably 45°. A cross section must be set out and drawn to show all of the materials as they are shown in the view from which the cross section was taken. The parts in cross section must show proper material(s) by hatching with regularly spaced parallel oblique strokes, the space between strokes being chosen on the basis of the total area to be hatched. The various parts of a cross section of the same item should be hatched in the same manner and should accurately and graphically indicate the nature of the material(s) that is illustrated in cross section. The hatching of juxtaposed different elements must be angled in a different way. In the case of large areas, hatching may be confined to an edging drawn around the entire inside of the outline of the area to be hatched. Different types of hatching should have different conventional meanings as regards the nature of a material seen in cross section.

(4) Alternate position . A moved position may be shown by a broken line superimposed upon a suitable view if this can be done without crowding; otherwise, a separate view must be used for this purpose.

(5) Modified forms . Modified forms of construction must be shown in separate views.

(i) Arrangement of views . One view must not be placed upon another or within the outline of another. All views on the same sheet should stand in the same direction and, if possible, stand so that they can be read with the sheet held in an upright position. If views wider than the width of the sheet are necessary for the clearest illustration of the invention, the sheet may be turned on its side so that the top of the sheet, with the appropriate top margin to be used as the heading space, is on the right - hand side. Words must appear in a horizontal, left - to - right fashion when the page is either upright or turned so that the top becomes the right side, except for graphs utilizing standard scientific convention to denote the axis of abscissas (of X) and the axis of ordinates (of Y).

(j) View for Official Gazette. One of the views should be suitable for publication in the Official Gazette as the illustration of the invention.

(k) Scale .

(1) The scale to which a drawing is made must be large enough to show the mechanism without crowding when the drawing is reduced in size to two - thirds in reproduction. Views of portions of the mechanism on a larger scale should be used when necessary to show details clearly. Two or more sheets may be used if one does not give sufficient room. The number of sheets should be kept to a minimum.

(2) When approved by the examiner, the scale of the drawing may be graphically represented. Indications such as "actual size" or "scale 1/2" on the drawings, are not permitted, since these lose their meaning with reproduction in a different format.

(3) Elements of the same view must be in proportion to each other, unless a difference in proportion is indispensable for the clarity of the view. Instead of showing elements in different proportion, a supplementary view may be added giving a larger - scale illustration of the element of the initial view. The enlarged element shown in the second view should be surrounded by a finely drawn or "dot - dash" circle in the first view indicating its location without obscuring the view.

(l) Character of lines, numbers, and letters. All drawings must be made by a process which will give them satisfactory reproduction characteristics. Every line, number, and letter must be durable, clean, black (except for color drawings), sufficiently dense and dark, and uniformly thick and well - defined. The weight of all lines and letters must be heavy enough to permit adequate reproduction. This requirement applies to all lines however fine, to shading, and to lines representing cut surfaces in sectional views. Lines and strokes of different thicknesses may be used in the same drawing where different thicknesses have a different meaning.

(m) Shading . The use of shading in views is encouraged if it aids in understanding the invention and if it does not reduce legibility. Shading is used to indicate the surface or shape of

Art Unit: 3727

spherical, cylindrical, and conical elements of an object. Flat parts may also be lightly shaded. Such shading is preferred in the case of parts shown in perspective, but not for cross sections. See paragraph (h)(3) of this section. Spaced lines for shading are preferred. These lines must be thin, as few in number as practicable, and they must contrast with the rest of the drawings. As a substitute for shading, heavy lines on the shade side of objects can be used except where they superimpose on each other or obscure reference characters. Light should come from the upper left corner at an angle of 45°. Surface delineations should preferably be shown by proper shading. Solid black shading areas are not permitted, except when used to represent bar graphs or color.

(p) Numbers, letters, and reference characters .

(1) Reference characters (numerals are preferred), sheet numbers, and view numbers must be plain and legible, and must not be used in association with brackets or inverted commas, or enclosed within outlines, e.g., encircled. They must be oriented in the same direction as the view so as to avoid having to rotate the sheet. Reference characters should be arranged to follow the profile of the object depicted.

(2) The English alphabet must be used for letters, except where another alphabet is customarily used, such as the Greek alphabet to indicate angles, wavelengths, and mathematical formulas.

(3) Numbers, letters, and reference characters must measure at least .32 cm. (1/8 inch) in height. They should not be placed in the drawing so as to interfere with its comprehension. Therefore, they should not cross or mingle with the lines. They should not be placed upon hatched or shaded surfaces. When necessary, such as indicating a surface or cross section, a reference character may be underlined and a blank space may be left in the hatching or shading where the character occurs so that it appears distinct.

(4) The same part of an invention appearing in more than one view of the drawing must always be designated by the same reference character, and the same reference character must never be used to designate different parts.

(5) Reference characters not mentioned in the description shall not appear in the drawings. Reference characters mentioned in the description must appear in the drawings.

(q) Lead lines . Lead lines are those lines between the reference characters and the details referred to. Such lines may be straight or curved and should be as short as possible. They must originate in the immediate proximity of the reference character and extend to the feature indicated. Lead lines must not cross each other. Lead lines are required for each reference character except for those which indicate the surface or cross section on which they are placed. Such a reference character must be underlined to make it clear that a lead line has not been left out by mistake. Lead lines must be executed in the same way as lines in the drawing. See paragraph (l) of this section.

Art Unit: 3727

(r) Arrows . Arrows may be used at the ends of lines, provided that their meaning is clear, as follows:

(1) On a lead line, a freestanding arrow to indicate the entire section towards which it points;

(2) On a lead line, an arrow touching a line to indicate the surface shown by the line looking along the direction of the arrow; or

(3) To show the direction of movement.

(t) Numbering of sheets of drawings . The sheets of drawings should be numbered in consecutive Arabic numerals, starting with 1, within the sight as defined in paragraph (g) of this section. These numbers, if present, must be placed in the middle of the top of the sheet, but not in the margin. The numbers can be placed on the right - hand side if the drawing extends too close to the middle of the top edge of the usable surface. The drawing sheet numbering must be clear and larger than the numbers used as reference characters to avoid confusion. The number of each sheet should be shown by two Arabic numerals placed on either side of an oblique line, with the first being the sheet number and the second being the total number of sheets of drawings, with no other marking.

(u) Numbering of views.

(1) The different views must be numbered in consecutive Arabic numerals, starting with 1, independent of the numbering of the sheets and, if possible, in the order in which they appear on the drawing sheet(s). Partial views intended to form one complete view, on one or several sheets, must be identified by the same number followed by a capital letter. View numbers must be preceded by the abbreviation "FIG." Where only a single view is used in an application to illustrate the claimed invention, it must not be numbered and the abbreviation "FIG." must not appear.

(2) Numbers and letters identifying the views must be simple and clear and must not be used in association with brackets, circles, or inverted commas. The view numbers must be larger than the numbers used for reference characters.

(w) Corrections . Any corrections on drawings submitted to the Office must be durable and permanent.

The drawings are objected:

- All description within the drawings must be removed.

Art Unit: 3727

- The various elements in the drawings must be labeled by numerals and these numerals must be discussed in detail in the specification. See the cited art of record.
- The various sections must be labeled accordingly and must indicate where the section taken place.
- All photographs must be replaced by drawings, and the specification must be corrected appropriately.

Specification

The following guidelines illustrate the preferred layout for the specification of a utility application. These guidelines are suggested for the applicant's use.

Arrangement of the Specification

As provided in 37 CFR 1.77(b), the specification of a utility application should include the following sections in order. Each of the lettered items should appear in upper case, without underlining or bold type, as a section heading. If no text follows the section heading, the phrase "Not Applicable" should follow the section heading:

- (a) TITLE OF THE INVENTION.
- (b) CROSS-REFERENCE TO RELATED APPLICATIONS.
- (c) STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT.
- (d) THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT
- (e) INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC (See 37 CFR 1.52(e)(5) and MPEP 608.05. Computer program listings (37 CFR 1.96(c)), "Sequence Listings" (37 CFR 1.821(c)), and tables having more than 50 pages of text are permitted to be submitted on compact discs.) or
REFERENCE TO A "MICROFICHE APPENDIX" (See MPEP § 608.05(a). "Microfiche Appendices" were accepted by the Office until March 1, 2001.)
- (f) BACKGROUND OF THE INVENTION.
 - (1) Field of the Invention.
 - (2) Description of Related Art including information disclosed under 37 CFR 1.97 and 1.98.
- (g) BRIEF SUMMARY OF THE INVENTION.

Art Unit: 3727

- (h) BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S).
- (i) DETAILED DESCRIPTION OF THE INVENTION.
- (j) CLAIM OR CLAIMS (commencing on a separate sheet).
- (k) ABSTRACT OF THE DISCLOSURE (commencing on a separate sheet).
- (l) SEQUENCE LISTING (See MPEP § 2424 and 37 CFR 1.821-1.825. A "Sequence Listing" is required on paper if the application discloses a nucleotide or amino acid sequence as defined in 37 CFR 1.821(a) and if the required "Sequence Listing" is not submitted as an electronic document on compact disc).

The specification filed on 10/04/04 has NOT been approved. The specification contains drawings inside the specification. Furthermore, the specification is not conform to the arrangement as set forth above.

The specification dated 03/31/04 is objected to:

- Applicant can delete section that is not applicable.
- Note that the title must be the same, e.g, "DETAILED DESCRIPTION" must be rewritten as "DETAILED DESCRIPTION OF THE INVENTION"
- The various elements in the drawings must be labeled by numerals and these numerals must be discussed in detail in the specification. See the cited art of record.

Claim Rejections - 35 USC § 112

1. Claims 1-12 are rejected as failing to define the invention in the manner required by 35 U.S.C. 112, second paragraph.

The claim(s) are narrative in form and replete with indefinite and functional or operational language. The structure which goes to make up the device must be clearly and positively specified. The structure must be organized and correlated in such a manner as to present a complete operative device. The claims must be in one sentence form only. Note the format of the claims in the patents cited.

The phrase "or like" renders the claims indefinite because the claims include elements not actually disclosed (those encompassed by "or the like"), thereby rendering the scope of the claims unascertainable. See MPEP § 2173.05(d).

"#" in claim 11 must be eliminate.

"said device frame" has no antecedent basis.

Claim Rejections - 35 USC § 102

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

3. Claims 1-12 rejected under 35 U.S.C. 102(b) as being anticipated by Carlton et al. (5762250). Carton et al. teaches a portable laptop that can be suspended as set forth in the claims.

Note that the device is adjustable via portions 90.

Regarding claim 7, it is noted that the functionality as set forth does not impart any structure over the device in Carlton.

Regarding claim 8, the laptop in Carlton can be plugged in as claimed. Again, there is no structural difference between the claimed laptop and the device in Carlton.

Regarding claims 9 and 10, the device in Carton can be used in the intended manner.

4. Claims 1-12 rejected under 35 U.S.C. 102(b) as being anticipated by Hrusoff et al. (5724225). Hruoff teaches a portable laptop that can be suspended as set forth in the claims.


Art Unit: 3727

5. Claims 1-12 rejected under 35 U.S.C. 102(b) as being anticipated by Sauer et al. (5938096). Sauer teaches a portable laptop that can be suspended as set forth in the claims.
6. Claims 1-12 rejected under 35 U.S.C. 102(b) as being anticipated by Lee (6349864). Lee teaches a portable laptop that can be suspended as set forth in the claims.
7. Claims 1-12 rejected under 35 U.S.C. 102(b) as being anticipated by Purpura (6659319). Purpura teaches a portable laptop that can be suspended as set forth in the claims.
8. Claims 1-12 rejected under 35 U.S.C. 102(b) as being anticipated by Merritt (6216927). Merritt teaches a portable laptop that can be suspended as set forth in the claims. Note the teachings with respect to portions 152 being a mesh material.
9. Claims 1-12 rejected under 35 U.S.C. 102(a) as being anticipated by Haber (2004/0200870). Haber teaches a portable laptop that can be suspended as set forth in the claims.
10. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Tri M. Mai whose telephone number is (571)272-4541. The examiner can normally be reached on 7:30am-5:00pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Nathan Newhouse can be reached on (571)272-4544. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 3727

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Tri M. Mai 
Primary Examiner
Art Unit 3727